E/D/19/447 Enquiry No.: USHA AMORPHOUS METALS LTD, INDIA (TOROIDAL- CORE DESIGN) Dated: 21/05/19 Rev.: 00 Dated: 21-05-19 Vitroperm 800 PHYSICAL SPECIFICATION: MATERIAL : Outer Diameter (Bare) (OD_B) mm 64.00 **DIMENSIONS:** Inner Diameter (Bare) (ID_B) mm 50.00 (HT_B) mm Height (Bare) 25.00 Height Outer Diameter (with Reinforcement) (OD_R) mm 67.40 (Max.) Inner Diameter (with Reinforcement) (ID_R) mm (Min.) 46.60 (Max.) Height (with Reinforcement) (HT_R) mm 28.20 Core Weight (Bare) (grams) 184.3 ± 3.0 % Core Weight (with Reinforcement) (grams) 197.3 ± 3.0 % **MAGNETIC CHARACTERISTICS:** OD Mean Magnetic Path (lm) cm 17.91 Net Cross Section Area 1.40 (Ac) cm² **XAAABBCC** UMNT Window Area 19.63 (Wa) cm² WHERE Area Product (Ap) cm⁴ 27.49 UM : Uaml Magnetics **ELECTRICAL SPECIFICATION:** Dimensions: mm : Nano Crystalline Ν : Toroidal Т Scale: Not To Scale AL Value : 78.60 μH (±30%) @ 10kHz Χ **Material Grade Projection:** Third Angle **Outer Dimention without casing** AAA AL Value : 19.65 μH (±30%) @ 100kHz BB : Inner Dimention without casing Special Instruction: CC : Height Dimention without Casing NOTE: Reinforcement: Plastic Box (Nylon 66 30% Glass Filled) A. ALL MEASUREMENTS ARE DONE AT ROOM TEMPERATURE Core Size: **UMNT-**V0645025 B. CONTINIOUS OPERATING TEMPERATURE 140°C Verification: Prepared By:_ Checked By: Feasibility Check and Approved By : ___ **REVISIONS DETAILS** NO. **REV NO** DATE ECN NO. Checked Approval Customer Approval: Company: Approver Name : Signature:_ Date: NOTICE/ DISCLAMER: THIS DRAWING, THE PROPERTY OF USHA AMORPHOUS METALS LTD.; INDIA IS FURNISHED. SUBJECT TO RETURN ON DEMAND AND THE CONDITION THAT THE INFORMATION AND TECHNOLOGY EMBEDED HEREIN SHALL NOT BE DISCLOSED OR USED AND THE DOCUMENT SHALL NOT BE REPRODUCED OR COPIED IN WHOLE OR IN PART EXCEPT AS PREVIOUSLY AUTHORISED IN WRITING; ANY PERSON RECEIVE OR OBSERVE THIS DOCUMENT WILL BE HELD STRICTLY LIABLE FOR ANY VIOLATION WHETHER OR NEGLIGENT.